

## SEDIMENT FILTERS ECOSOFT FP

### APPLICATION:

Water treatment for houses, hotels, cafes, restaurants, boilers, industrial processes

### FILTER MEDIA:

Filter Ag Plus®

### REDUCES:

Silt, sand, rust, scale (turbidity)

### CONTROL VALVE:

Time controlled Ecosoft WS 1.0" CT / WS 1.25" CE (Clack Corporation, USA)

### KEY FEATURES:

1. Ready to use — fully equipped filter
2. Transparent water — no mud or sand sediments on the surface of sanitary ware, longer service life of home appliances and heating systems
3. Easy-to-use — advanced control valve Ecosoft CT/CE with quick and easy programming procedure
5. Reliable and long-term operation thanks to high-quality Clack Corporation components
6. CE marked and confirmed to be safe in accordance with EC New Approach Directives

### COMPONENTS:

- Fully assembled Ecosoft WS 1.0" CT / WS 1.25" CE control valve (control valve, DLFC, top distributor, AC transformer, funnel, user manual)
- Filter tank (with riser pipe and bottom distributor)
- Filter media



*Anti-condensation tank cover is not included*

### SEDIMENT FILTERS ECOSOFT FP (FILTER-AG PLUS®)

Code	Q, m <sup>3</sup> /h (GPH) (nominal)	Volume of media, L (ft <sup>3</sup> )	Inlet/outlet size
FP1054CT	0.60 (160)	28.3 (1.0)	1" NPT
FP1252CT	0.85 (225)	56.6 (2.0)	
FP1354CT	1.0 (270)	84.9 (3.0)	
FP1465CT	1.2 (315)	113.2 (4.0)	
FP1665CT	1.55 (410)	169.8 (6.0)	
FP2162CE	2.65 (700)		1.25" NPT