

TECHNICAL SPECIFICATIONS:

Parameter	FU1054CE	FU1252CE	FU1354CE	FU1465CE	FU1665CE
Operating/maximum flow rate, m ³ /h	2.0/2.5	2.8/3.6	3.5/4.5	4.0/5.0	5.0/6.0
Mængde af High Grade resin pr. tryktank, l	37	62	75	100	125
Volume kapacitet, m ³ @ 250 mg/l CaCO ₃ hårdhed	7.5	12.5	15.0	20.0	25.0
Saltforbrug per regenerering, kg	4–6	6–10	8–12	10–16	12–20
Vandforbrug p. regenerering, m ³	0.37	0.62	0.75	1.0	1.25
Tid for regeneration, minutter	80–110				
Tryktab i service mode, bar	0.5–1.0				
Vandtryk, bar	2–6				
Electrisk forsyning	230 V, 50 Hz				
Strømforbrug under regenerering, W	30				
Inlet/outlet rørforbindelse	1"				
Tørvægt kg	60	85	95	120	145
Dimensioner, (Bredde × Dybde × Højde, cm)	130 × 45 × 160	140 × 45 × 155	145 × 45 × 160	150 × 50 × 190	160 × 50 × 190

Krav til vandkvalitet:

Hårdhed	750 mg/l CaCO ₃
Jern	0.2 mg/l
Mangan	0.05 mg/l
Chemical Oxygen Demand	5 mg/l O ₂
Sediment forfilter	100 µm
Vandtemperatur	+4...+30 °C