

ECOSOFT ROBUST 3000 REVERSE OSMOSIS FILTER

APPLICATION:

Cafés, restaurants, water production, pharmacies, laboratories, small breweries, summer houses

KEY FEATURES:

- Consistent high capacity up to 150 liters per hour
- Recovery rate 50% — filter is economical and environmentally-friendly
- Direct flow RO system
- Designed for tankless operation
- Built-in pressure gauges indicating pre-filters and membrane conditions
- CE marked and confirmed to be safe in accordance with EC New Approach Directives



((ec))

Can be equipped with controller with Econnect feature for permanent online access to the filter *

SPECIFICATION:

Code	Flow capacity ¹ , LPH (GPH)	Water consumption, LPH (GPH)	Power supply	Power consumption, kW (hp)	Dimensions, H x W x D, mm (in)
ROBUST3000	145–150 (38–40)	290–310 (77–82)	230 V, 50 Hz	0.25 (0.34)	480 × 530 × 400 (18.9 × 20.1 × 15.8)

¹ At 25 °C feed water temperature, TDS 1000 mg/L

COMPONENTS:

- RObus 3000 reverse osmosis filter
- Connection fittings pack
- Service wrenches
- User manual

FILTRATION TECHNOLOGY:

- BB10 GAC coconut shell carbon filter
- Ecosoft RO membrane element (2 pcs.)
- BB10 GAC coconut shell carbon filter

ECOSOFT ROBUST 3000 REVERSE OSMOSIS FILTER

Code	Product	Membrane	Pieces on pallet
ROBUST3000	Ecosoft RObus 3000 reverse osmosis filter	2 x CSV3012500ECO	8

ROBUST 3000 REPLACEMENT FILTERS

Code	Product
CHV4510ECO	Ecosoft granular activated carbon replacement filter 4.5"×10"
CSV3012500ECO	Ecosoft 500 GPD membrane element

* Option

** List prices are without VAT

Minimum order is 1 pallet of any product